



NITRO 525RS

Capacities determined by ASAE Std S324.1

Carrying Capacity	15
Heaped (cu. ft.) (with Optional Silage Extension)	555 N/A
Struck Level (cu. ft.) (with Optional Silage Extension)	407 N/A
Inside Dimensions (Inside width between flare 89")	62.5"W x 45.5"D x 218"L
Overall Length	27.5'
Overall Outside Width (Single Axle)	N/A
Overall Outside Width (Tandem Axle)	116"
Loading Height (Single Axle) (with Optional Silage Extension)	N/A N/A
Loading Height (Tandem Axle) (with Optional Silage Extension)	80" N/A

Nitro RS Spreaders are available only with tandem axles.

Wheel Hub Capacity (Tandem Axle)	12,000lbs (8-bolt) x4
Tandem Tire Sizes	425/22.5 Recap Truck Tires or 550/45-22.5 Floatation Tires or 700/50-26.5 Floatation Tires
Wheel Hub Capacity (Single Axle)	N/A
Single Tire Sizes	N/A
Beater Diameter	34
Beater Speed	420 RPM
PTO Speed	1000 RPM
Apron Chain Link Dia.	5/8"
Shipping Weight	11,000lbs.
Required Tractor PTO HP	125
Brakes Available	Yes